

# ProSeries™ HI Side & Top

## ECONOMICAL AND RELIABLE

- **Hard-wearing:** polyethylene-injected, heat-fusion welded filters
- **Filters particularly suitable for above-ground and smaller-sized pools (up to 65 m³)**
- **Wide range of products (6 in total: 3 Side and 3 Top)** to suit all pool configurations
- **Easy to maintain and use,** thanks to its transparent polycarbonate screw-on cover
- **Circular base for optimal filter seating**



ProSeries™ HI Side

ProSeries™ HI Top




6-position valve




180 mm diameter threaded opening for simpler maintenance operations



Circular base for perfect filter stability



Dimensions of HI Side filter



Dimensions of HI Top filter

### Technical Specifications

Max. water temperature	50°C
Operating pressure	0.5 - 1.3 bar
Maximum pressure	2.0 bar
Connection	1.5"
Tank / Arms / Unions / Cover	PP/PP/ABS/SAN®, suitable for saltwater
Granulometry of filtration media	0.4 ÷ 0.8 mm

	Flow rate	Diameter ø	In/Out	Filtration area	Empty weight	Sand	Dimensions					Item
							A	B	C	D	E	
PROSERIES™ HI SIDE	6 m³/h	400	1" ½	0.13 m²	10.5 kg	50 kg	266 mm	391 mm	651 mm	503 mm	453 mm	S160SIE
	9.5 m³/h	500	1" ½	0.19 m²	12.5 kg	100 kg	345 mm	470 mm	808 mm	503 mm	553 mm	S210SIE
	14 m³/h	600	1" ½	0.28 m²	15.5 kg	125 kg	391 mm	516 mm	891 mm	503 mm	653 mm	S240SIE
PROSERIES™ HI TOP	6 m³/h	400	1" ½	0.13 m²	10 kg	50 kg	720 mm	780 mm	922 mm	503 mm	453 mm	S160TIE
	9.5 m³/h	500	1" ½	0.19 m²	12 kg	100 kg	877 mm	937 mm	1079 mm	503 mm	553 mm	S210TIE
	14 m³/h	600	1" ½	0.28 m²	15 kg	125 kg	960 mm	1020 mm	1161 mm	503 mm	653 mm	S240TIE